

13.05.04

REC'D 13 MAY 2004
WIPO
PCT

PA 1042233

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

July 22, 2003

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/471,702

FILING DATE: May 19, 2003

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



T. LAWRENCE
Certifying Officer

Best Available Copy

05/19/03



Please type a plus sign (+) inside this box → ☐

05-20-03 60471702

Approved for use through 10/31/2002. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label No. EV 335 816 512 US		Date of Deposit: May 19, 2003	
INVENTOR(S)			
Given Name (first and middle (if any))	Family Name or Surname	Residence (City and either State or Foreign Country)	
George Giang	Marmaropoulos Vu	Yorktown Heights, NY Ossining, NY	
<input checked="" type="checkbox"/> Additional inventors are being named on the <u>2nd</u> separately numbered sheets attached hereto			
TITLE OF THE INVENTION (280 characters max)			
CONDUCTIVE BUTTONHOLE INTERCONNECT			
CORRESPONDENCE ADDRESS			
Direct all correspondence to:			
<input checked="" type="checkbox"/> Customer Number		24737	→ <div style="border: 1px solid black; padding: 5px; display: inline-block;">*24737*</div>
OR Type Customer Number here			
<input type="checkbox"/> Firm or Individual Name	PHILIPS ELECTRONICS NORTH AMERICA CORPORATION		
Address	580 WHITE PLAINS ROAD		
Address			
City	TARRYTOWN	State	NY
Country	USA	ZIP	10591
Telephone	(914) 333-9608	Fax	(914) 332-0615
ENCLOSED APPLICATION PARTS (check all that apply)			
<input checked="" type="checkbox"/> Specification Number of Pages	13	<input type="checkbox"/> CD(s), Number	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets	5	<input type="checkbox"/> Other (specify)	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76			
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)			
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.			
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees			
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: 14-1270			
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.			
FILING FEE AMOUNT (\$) 160.00			
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.			
<input checked="" type="checkbox"/> No.			
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____			

Respectfully submitted,
SIGNATURE

Date 5/19/03

TYPED or PRINTED NAME AARON WAXLER

REGISTRATION NO.: 48,027
(if appropriate)

TELEPHONE (914) 333-9608

Docket Number: US030124

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C., 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

J1046 U.S. PTO
60/471702

PROVISIONAL APPLICATION COVER SHEET**Additional Page**

PTO/SB/16 (02-01)

Approved for use through 10/31/2002. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Docket Number	US030124	Type a plus sign (+) inside this box →	+
INVENTOR(S)/APPLICANT(S)			
Given Name (first and middle [if any])	Family or Surname	Residence (City and either State or Foreign Country)	
Jack	Mama	Amuhurst Road, London, England	

Number 2 of 2

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

GEORGE MARMAROPOULOS, ET AL.

US030124

Serial No.

Group Art Unit

Filed: CONCURRENTLY

Ex.

Title: CONDUCTIVE BUTTONHOLE INTERCONNECT


Commissioner for Patents
Alexandria, VA 22313-1450AUTHORIZATION PURSUANT TO 37 CFR §1.136(a)(3)
AND TO CHARGE DEPOSIT ACCOUNT

Sir:

The Commissioner is hereby requested and authorized to treat any concurrent or future reply in this application requiring a petition for extension of time for its timely submission, as incorporating a petition for extension of time for the appropriate length of time.

Please charge any additional fees which may now or in the future be required in this application, including extension of time fees, but excluding the issue fee unless explicitly requested to do so, and credit any overpayment, to Deposit Account No. 14-1270.

Respectfully submitted,

By 
Aaron Waxler, Reg. 48,027...
Patent Agent
(914) 333-9608

703748

CONDUCTIVE BUTTONHOLE INTERCONNECT**BACKGROUND OF THE INVENTION**5 1. Field of the Invention

This invention relates to an interconnect system intended to permit the connection of an electronic device or power source to a fabric electric circuit embedded in a garment. More specifically, the invention relates to an
10 electrical interconnect system having an electrical interconnect device incorporated into the garment in a location or locations most conveniently accessible to the wearer.

15 2. Description of the Invention

Integrated electrical switches for use in clothing are typically sewn, glued, or otherwise mounted to clothing using standard "off the shelf" electric components, deemed well known in the art. However, to the best of the current
20 inventors' knowledge, the prior art devices in wearable electronic applications do not address the problem of assuring simple and intuitive electrical connectors so as to be fashionable.

25 Therefore, the present invention relates to garment electrical connectors that can be realized in simple,

703748

intuitive, reliable, and inexpensive implementation. Moreover, the present invention facilitates manufacture of such connectors as close as possible to the manufacturing techniques used in the garment industry for widespread
5 acceptance within the garment manufacturing industry.

SUMMARY OF THE INVENTION

The present invention discloses a wearable garment with
10 an electrical interconnect system, which includes a buttonhole having at least one conductive outer edge mounted to the body of the garment and a connector detachably coupled to the conductive areas of the buttonhole for coupling an external electronic device or power source. The electrical
15 interconnect system of this invention incorporates a buttonhole that can be easily manufactured with conventional buttonhole machines. The buttonhole is electrically coupled to a fabric circuit integrated in the garment material.

According to one aspect of the invention, a garment of
20 desired form and function can be constructed in a conventional manner using readily available fabrics and materials, and the electrical interconnect system can be positioned advantageously within a buttonhole that permits easy activation manually by a person. Necessary connection
25 cables or cords can extend from the interconnect system for connection to an electronic device embedded in the garment

703748

material or an external power source.

According to another aspect of the invention, a button having at least one conductive outer edge is attached to a first garment layer, which in turn is electrically coupled to
5 a first fabric circuit integrated in the garment material. The button is releasably coupled to a button hole having at least one conductive outer edge attached to a second fabric circuit integrated in a second garment layer, such that the first and second fabric circuits of the respective layers can
10 be electrically coupled together.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates an embodiment of an electrical interconnect system in accordance with this invention.

15 Figure 2 illustrates the electrical interconnect system of Figure 1 in accordance with a first embodiment of this invention.

Figure 3 is a detailed construction of the electrical interconnect system of Figure 1 and a connector in accordance
20 with the first embodiment of this invention.

Figure 4 illustrates the electrical interconnect system of Figure 1 in accordance with a second embodiment of this invention.

Figure 5 is a detailed construction of the electrical
25 interconnect system of Figure 1 and a connector in accordance with the second embodiment of this invention.

703748

DETAILED DESCRIPTION OF THE DISCLOSED EMBODIMENT

In the following description, for purposes of explanation rather than limitation, specific details are set forth such as the particular architecture, interfaces, techniques, etc., in order to provide a thorough understanding of the present invention. For purposes of simplicity and clarity, detailed descriptions of well-known devices, circuits, and methods are omitted so as not to obscure the description of the present invention with unnecessary detail.

Referring now to Figure 1 of the drawings, a wearable garment 2 in accordance with this invention includes an electrical interconnect device 12 and a connector 16. The connector 16 comprises a cable extending from the interconnect device 12, with the cable being coupled to a power source or other external electronic device. In the embodiment illustrated in Figure 1, the wearable garment 2 has the form of a conventional sleeveless top shirt, although it will be understood readily that the shirt alternatively may be either long-sleeved, short-sleeved, vest, or jacket, for example. In addition, the materials of garment 2 may be either natural or synthetic, and the fabric created from such materials can be either woven or sheet-formed in any well-known manner.

Referring to Figure 2, one side of the garment 2 is

703748

provided with the electrical interconnect system 12, which includes an opening 10 defined by an outer ring 11 having one or more conductive area 11a at both ends thereof. The provision of the opening 10 to the fabric is well known to the skilled person, as are variations in such attachment detail. The outer ring 11 is electrically coupled to a conductive track of a fabric circuit 4, which may be provided in the form of loops to receive or otherwise engage equipment considered ancillary to the interconnect system 12, such as an external heart-monitoring device, external defibrillator, or other electronic devices. Alternatively, such ancillary equipment or other electronic devices may be integrated in the garment 2 and used in conjunction with the interconnect system 12 for transmitting the desired signals or power in any well-known manner.

Referring to Figure 3, the connector 16 that allows the connection of a power supply or an external electronic device as described above comprises a button connector 40 having one or more conductive surfaces 40a that may be electrically coupled to the conductive areas 11a of the outer ring 11 for transmitting signals or power. As shown, the button connector 40 has a shape adapted to interconnect releasably the respective conductive areas physically and electrically with each other. Accordingly, a wearer can engage an ancillary device readily by merely mounting the button connector 40 with one hand to the proper opening of the

703748

garment. It will be understood readily by those having skill in this art, that in this embodiment of the invention, any connecting cable 16 extending from the button connector 40 can be coupled without difficulty to an ancillary device such as a cell phone, radio, pager, GPS device, personal communication assistant, or other signal transmitter or duplex interactive system, carried anywhere on the person of the wearer of the band.

Figure 4 illustrates the electrical interconnect system 12 according to another embodiment of this invention. As shown, one side of the garment 2 is provided with a button component 20 having one or more conductive area 20a. The conductive area 20a of the button component 20 is electrically coupled to a conductive track of a fabric circuit 4. It is noted that the button component 20 in proper position on garment 2 formed by ordinary garment materials can be accomplished easily using well-known sewing and or other fabric-attachment techniques. The materials of such garment may be either natural or synthetic, and the fabric created from such materials may be either woven or sheet-formed in any well-known manner.

Referring to Figure 5, the button component 20 may be joined together with the outer ring 11a with a releasable locking action by the wearer. In this embodiment, a wearer can engage the interconnect system 12 readily by merely fastening the button connector 20 of a first layer of the

703748

garment 2 to the outer ring 12 of a second layer of the garment 2. The two layers joined together can be made to be water-resistant or waterproof in the area forming the interconnect system 12 to provide additional protection.

5 It should be noted that the conductive track of the fabric circuit 4 coupled to the button connector 20 may be provided in the form of loops to receive or otherwise engage equipment considered ancillary to the interconnect system 12, such as a heart-monitoring device, defibrillator, and other
10 electronic devices that are integrated in the garment 2 and used in conjunction with the interconnect system 12 for transmitting the desired signals or power in any well-known manner.

 While the preferred embodiments of the present invention
15 have been illustrated and described, it will be understood by those skilled in the art that various changes and modifications can be made, and equivalents may be substituted for elements thereof without departing from the true scope of the present invention. For example, although an elliptical-
20 shaped interconnect system is shown for illustrative purposes, it is to be understood that the present invention can support other shapes. Thus, the shape of an interconnect system in the drawings should not impose limitations on the scope of the invention. Therefore, it is intended that the
25 present invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out the

703748

present invention, but that the present invention include all
embodiments falling within the scope of the appended claims.

5

10

15

20

25

703748

What is claimed is:

1. An interconnect apparatus comprising:
a wearable garment having a body structure; and
at least one interconnect element having at least one electrically conductive contact portion and an opening, said interconnect device coupled to a fabric circuit integrated in said garment.
2. The interconnect apparatus of Claim 1, further comprising a connector having at least one electrically conductive contact portion, said connector being releasably coupled to said interconnect element.
3. The interconnect apparatus of Claim 2, wherein said connector further comprises a cable extending therefrom.
4. The interconnect apparatus of Claim 3, wherein said cable serves as a coupling to an electronic device.
5. The interconnect apparatus of Claim 3, wherein said cable serves as a coupling to a power source.

703748

6. The interconnect apparatus of Claim 2, wherein said interconnect device is mounted on the outer surface of said garment for engaging and supporting units ancillary to transmitting electronic signals.

7. An interconnect apparatus comprising:

a wearable garment having a body structure;

at least one interconnect element having at least one electrically conductive contact portion coupled to a first fabric circuit integrated in a first layer of said garment; and,

a connecting element having at least one electrically conductive contact portion coupled to a second fabric circuit integrated in a second layer of said garment,

wherein said interconnect element engages the connecting element via a releasable locking action so that the respective conductive contact portions come in contact electrically.

8. The interconnect apparatus of Claim 7, wherein said first and second fabric circuits are coupled to a signaling device.

9. The interconnect apparatus of Claim 7, wherein said first and second fabric circuits are coupled to electronic devices integrated in the body structure of said garment.

703748

10. The interconnect apparatus of Claim 6, wherein said connector is a button.

11. A method for permitting a person to activate an electronic device conveniently, said method comprising the steps of:

attaching at least one fabric circuit in a wearable garment;

mounting an interconnect device having at least one conductive contact portion to said wearable garment;

dressings said person in said wearable garment; and,

selectively coupling a connector having at least one conductive contact portion to said interconnect device to serve as a coupling to an electronic device or a power source.

12. A method for permitting a person to activate an electronic device conveniently, said method comprising the steps of:

attaching at least one fabric circuit in a first layer and a second layer of a wearable garment;

mounting an interconnect device having at least one conductive contact portion to the first layer of said wearable garment;

mounting a connector having at least one conductive

703748

contact portion to the second layer of said wearable garment;

 dressing said person in said wearable garment; and,
 enclosing two layers of said wearable garment by
engaging said connector to said interconnect device so that
the respective conductive contact portions come in contact
electrically.

703748

ABSTRACT OF THE DISCLOSURE

A wearable garment, usable by athletes, workers, and the elderly or infirm, incorporates an easily operated manual interconnect device, so that a user wearing the garment can operate the interconnect device by merely coupling a connector, which is in turn coupled to a power source or external electronic device. Through a releasable locking action by the user, the connector is electrically coupled to the interconnect device, which is coupled to a fabric circuit integrated in the garment, such that operation of a locking action activates related ancillary equipment such as power supplies or electronic devices.




FIG. 1




FIG. 2




FIG. 4




FIG. 5

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.